

Bill

SPECIFICATIONS

Shipped 1/28/83

for a

TWO MANUAL AND PEDAL PIPE ORGAN

Designed For

PEACE LUTHERAN CHURCH

BELLEVILLE, ILLINOIS

5930

CONSOLE Detached - Drawknob - Built to AGO Specs.

DISPLAY FRONT Casework as per print

GREAT — 2 3/4" W.P.

- 8' Principal 45 4/15 61 Pipes ZINC + 50/50
- 8' Holzgedeckt CUT LOW 61 Pipes WOOD - Trebles = 40% TIN
- 8' Gemshorn
- 4' Principal 12 Pipes
- 4' Rohrflöte
- 2' Octave 12 Pipes
- 2' Flachflöte 24 Pipes
- III Mixture from R. Fl. + Gemsh. (like FA) 12 Pipes
- 8' Trompete
- Chimes (used chimes) 25 Notes

SWELL — 4" W.P.

- AL- 8' Rohrflöte 48 1/4 61 Pipes 40% TIN - WOOD Bass like 5287.
- B.I.S. 8' Gemshorn 48 (at 8') [1/2 in 18TH] 4/15 49 Pipes 1/2 T. 40% TIN
- AL- 8' Gemshorn Celeste TC like Gemshorn 49 Pipes 40% TIN
- 4' Rohrflöte 12 Pipes
- 4' Erzähler Gemshorn 12 Pipes
- 2 2/3' Quint
- 2' Blockflöte 12 Pipes
- 8' Trompete 3" {SCHALMEI} {SHALLOTS} 61 Pipes ZINC + HOYT
- Tremolo

PEDAL

- 2 3/4" W.P. — 16' Rohr Gedeckt #2 12 Pipes WOOD.
- 8' Principal
- 8' Rohrflöte
- 4' Choral Bass
- 4' Rohrflöte
- 4" W.P. — 16' Posaune 5" (graduate to match 8") {SCHALMEI} {SHALLOTS} 12 Pipes Keep Soft
- 8' Trompete
- 4' Klarine

COUPLERS

- Great to Pedal
- Swell to Pedal
- Swell to Great 16'
- Swell to Great 8'
- Swell to Great 4'
- Swell to Swell 16'
- Swell Unison
- Swell to Swell 4'

COMBINATION PISTONS

- Five General Pistons affecting entire organ.
- Three Position Selector Switch providing fifteen general piston settings
- General Cancel

ACCESSORIES

- Balanced Swell Expression Pedal
- Crescendo Pedal and Indicator
- Lock on Combination Setter
- Wind Indicator Light
- Music Rack Light and Pedal Light
- Organ Bench with Music Compartment ...
- Expression Enclosure for Swell
- Blower Enclosure
- Blower and Rectifier
- 25 Feet Cable