

TWO MANUAL AND PEDAL PIPE ORGAN

Designed For
TUSCOLA METHODIST CHURCH
TUSCOLA, ILLINOIS

Bobby

4732

MANUAL COMPASS C C TO C 4 61 NOTES

PEDAL COMPASS C C C TO G 32 NOTES

SUBMITTED May 7, 1966

CONSOLE Detached Drawknob controls, Style #6, built to AGO Specifications

DISPLAY FRONT None Required

CHAMBER PREPARATIONS: To be prepared by Purchaser

PITCH: International A - 440

GREAT ORGAN (Unenclosed Non-expressive)

* 8'	Principal	47	1/4	61	Pipes slot	49
* 8'	Rohrflöte	50	3/4	61	Pipes	49
8'	Viole (From Swell)			61	Notes	
* 4'	Octave	60	1/2	61	Pipes slot	61
* 4'	Spitzflöte	57	1/5	61	Pipes	61
* 2'	Blockflöte	71	3/4	61	Pipes	61
* 11	Furniture	84-91	1/4-3/4	122	Pipes	122
	Chimes (Prepared for)					

(use of slots - provide)

*1-18 22-26
19-40 19-22
45-54 15-19
55-61 12-15*

Keep soft

SWELL ORGAN

(To be enclosed in a resonant wood expression chamber, to be provided and erected by organ builder.)

8'	Gedeckt	CUT HIGH		61	Pipes	WOOD 49
8'	Viole	58		61	Pipes	slot 49
8'	Viole Celeste	T. C. 60		49	Pipes	61
* 4'	Koppelflöte	61	1/5	61	Pipes	49
* 2 2/3'	Nazard	63	3/5	61	Pipes	49
* 2'	Principal	70	3/4	61	Pipes	40% TIN
* 1 3/5'	Terz	72 N. Horn Sa.	2/12-1/6	61	Pipes	49
8'	Trompette	2 5/8" FR. NARROW slot		61	Pipes	
4'	Trompette			12	Pipes	
	Tremulant					

PEDAL ORGAN

16'	Quintbasse	FT		32	Pipes	20
8'	Bourdon	48	2/3	32	Pipes	WOOD BASS
* 4'	Choralbass	58	1/4	32	Pipes	slot 32
* 11 Rk.	Mixture	Reuschpfeife	2 2/3'-2'	64	Pipes	66-71 3/4-1/4
16'	Posaune	5" ENGL.		32	Pipes	64

COUPLERS

Great to Great	4'	Swell Union	Off
Swell to Great	4'	Swell to Swell	16'
Swell to Great	8'	Great to Pedal	8'
Swell to Great	16'	Swell to Pedal	4'
Swell to Swell	4'	Swell to Pedal	8'

COMBINATION ACTION

(The Preferred Remote Controlled Capture System, Visible affecting drawknobs.)

Four Pistons affecting Great Stops and Couplers - Thumb

Cancel

Four Pistons affecting Swell Stops and Couplers - Thumb

Cancel

Four Pistons affecting Pedal Stops and Couplers - Toe & Thumb

Cancel

Four General Pistons affecting entire organ Thumb and

duplicated by Toe Studs

General Cancel

Sforzando Piston, affecting entire organ Thumb and Toe

ACCESSORIES

Resonant wood Swell expression chamber with laminated louvers, to be provided and erected by organ builder.

Balanced Swell Expression Pedal to Swell enclosure

Balanced crescendo pedal, adjustable at the console

Progressive, multiple light crescendo indicator.

Wind indicator light

Light on Music rack, built - in music rack within console

Sforzando indicator light

Style #6 console with roll top with lock

Organ bench with music storage and backrest

Separate wind regulators for all chest and reeds, as required for steady air.

Motor, blower and rectifier of adequate capacity.

Blower enclosure with soundproof baffle box

Twenty-five feet of main organ cable to be

supplied, additional cable supplied at

\$4.00 per ft., as required to be pulled and connected by purchaser.

** = open to*