

SPECIFICATIONS

For a

Two Manual and Pedal Pipe Organ

Manual Compass CC to C4....61 Notes

Pedal Compass CCC to G.....32 Notes

CONSOLE: Drawknobs, 60 degree Jamb. Built to AGO specifications.

Standard Keys.

DISPLAY FRONT: Finished Expression Enclosure for Swell.

PREPARATION OF ORGAN SPACE by Purchaser

GREAT

8'	Principal	(exposed)
8'	Rohrgedeckt	
8'	Gemshorn	[D]
8'	Flute Celeste II	[D]
4'	Octave	(exposed)
4'	Flöte	
2'	Super Octave	(exposed)
2'	Spitzoctave	
III	Mixture	[D]
8'	Trompette	[D]
	Chimes	[D]
	Harp	[D]
	Blank	

SWELL

8'	Geigan Principal	[TC]
8'	Rohrgedeckt	
8'	Gemshorn Celeste II	[D]
4'	Geigan Octave	
4'	Flöte	
4'	Gemshorn	[D]
2 2/3'	Nazard	
2'	Octave	(exposed)
2'	Blockflöte	
1 1/3'	Larigot	
1'	Sifflöte	
8'	Trompette	[D]
8'	Oboe	[D]
	Tremolo	

PEDAL

16'	Principal	[D]
16'	Subbass	[D]
8'	Principal	(exposed)
8'	Rohrgedeckt	
4'	Choralbass	(exposed)
16'	Bombarde	[D]
8'	Trompette	[D]
4'	Schaelmei	[D]
	Blank	

RESOURCES

8'	Rohrgedeckt	85 Pipes
8'	Principal	85 Pipes
8'	Geigan Principal (TC)	73 Pipes

[D] = Digital Voices

COUPLERS

Swell to Great 16'	Swell Unison
Swell to Great 8'	Swell to Swell 4'
Swell to Great 4'	Great to Pedal 8'
Swell to Swell 16'	Swell to Pedal 8'

COMBINATION PISTONS

5 GENERAL PISTONS affecting the entire Organ
Duplicate by Toe Studs
GENERAL CANCEL
3 MEMORY LEVELS with Selector
Setter Piston

ACCESSORIES

Balanced Expression Pedal	Crescendo Pedal
Great to Pedal Reversible - Thumb	Crescendo Indicator Light
Sforzando Reversible - Thumb and Toe	Sforzando Indicator Light
Lock on Combination Setter	Wind Indicator Light
Wicks Solid-State Relay System	Music Rack Light
6 Pistons prepared for MIDI	Pedal Light
Digital System (Voices marked "[D]")	Blower
Includes Amplifier and Speakers	Rectifier
Stops, Coupler and Pistons of Hardwood	Locking Motor Switch
Organ Bench with Music Compartment	Wicks Keying System
25 Feet of Main Cable from Console to Organ	

