

Shipped Jan. 11 - 1964

neg

SPECIFICATIONS
For A
THREE MANUAL AND PEDAL PIPE ORGAN
Designed For
Seventh Church Christ Scientist
Kansas City, Missouri

4342

MANUAL COMPASS CC TO C4 61 NOTES
PEDAL COMPASS CCC TO G 32 NOTES
SUBMITTED 19

CONSOLE Three Manual Draw Knob No. #6

DISPLAY FRONT Case work around exposed chests (40 sq. ft.) Bronze Slides

The voicing of the entire organ, except strings, shall be of the latest style with "Chiff" in the sound.

50/50

		GREAT ORGAN (Exposed) 2" W.P.			
1.	X 8'	Principal.	M.B. open toe	47	.61 Pipes
2.	X 8'	Bourdon.	BoB open toe	52	.61 Pipes
3.	X 4'	Spitzflöte	BoB open toe	59	.61 Pipes
4.	X 4'	Octave.	M.B. open toe	60	.61 Pipes
5.	X 2'	Super Octave	Geo. R. open toe	72	.61 Pipes
6.	X 1-1/3'	Octave Quinte	Geo. R. open toe	79	.61 Pipes
7.		Chimes.	(Choir)		.21 Notes
		SWELL ORGAN (Enclosed)			
8.	X 8'	Rohrflöte.	Geo. R. open toe	50	.61 Pipes WOOD Bass REG. HIGH cut-up
9.	X 8'	Spitzgamba	Geo. R. 3/4 TAPER	54 SLOT 7/8	.61 Pipes
10.	X 8'	Gamba Celeste T.C.	Geo. R.	58 SLOT 1/2	.49 Pipes
11.	X 4'	Hohlflöte.	M.B.	WOOD	.61 Pipes
12.	2'	Blockflöte			.12 Pipes
13.	X 1-3/5'	Tierce.	M.B. open toe	72 2 1/2 1/2	.61 Pipes NACHTHORN SC.
14.	8'	Trompette		3 1/2	.61 Pipes
15.	4'	Rohrschalmei		REG. 40 REEDS	.61 Pipes
16.		Tremulant			
		CHOIR ORGAN (Enclosed) 3" W.P.			
17.	X 8'	Gemshorn.	CAN. open toe	48 7/8	.61 Pipes
18.	X 8'	Gemshorn Celeste T.C.	CAN.	48 7/8	.49 Pipes
19.	8'	Chant Flute.	M.B.	WOOD	.61 Pipes
20.	X 4'	Prestant.	CAN. open toe	60 SLOT 3/4	.61 Pipes
21.	8'	Krummhorn.		SMALL SCALE	.61 Pipes SMALL MEI SMALLOTS?
22.		Chimes.	(Use Present Chimes & Action)		.21 Tubes
23.		Tremulant			
		POSITIVE ORGAN (Exposed) 2" W.P.			
24.	8'	Nazon Flute.	M.B.	WOOD	.61 Pipes
25.	X 4'	Koppelflöte	BoB open toe	61 1/5	.61 Pipes
26.	X 2-2/3'	Nazat.	BoB open toe 1/3 TAPER	64 1/5	.61 Pipes
27.	X 2'	Principal.	M.B. open toe	71 3/4	.61 Pipes
28.	1'	Piccolo.	JOHN open toe	80 1/5	.61 Pipes
29.	III Rk.	Cymbal	BoB. 33-36-40 open toe	102-107-114	183 Pipes
		PEDAL ORGAN			
30.	16'	4" W.P. Bourdon.	M.B.	#1	.32 Pipes
31.	16'	Rohrflöte.	#8	#3	.32 Pipes SOFT WIND
32.	X 8'	2" W.P. Principal.	M.B. open toe	46 2/3	.32 Pipes
33.	8'	Gemshorn			.32 Notes
34.	4'	Spitzflöte			.32 Notes
35.	8'	Spitzgamba			.32 Notes
36.	5-1/3'	Quinte			.32 Notes
37.	4'	Octave			.32 Notes
38.	4'	2" W.P. Nachthorn.	JOHN open toe	56 2/3 1/2	.32 Pipes
39.	2'	Principal.			.32 Notes
40.	4'	Rohrschalmei			.32 Notes
41.	8'	Trompette			.32 Notes
42.	III Rk.	Cymbal			.32 Notes

1-8
9-16
17-23
24-31
32-38
39-46
47-54
55-61

S P E C I F I C A T I O N S

Page 2

COUPLERS

4342

Great to Pedal	Swell to Pedal
Choir to Pedal	Positive on Pedal
Positive on Great	Positive on Swell
Positive on Choir	Swell to Swell 16'
Swell to Swell 4'	Swell to Great 16'
Swell to Great 8'	Swell to Great 4'
Choir to Great 16'	Choir to Great 8'
Choir to Great 4'	Great to Great 16'
Great to Great 4'	Choir to Choir 16'
Choir to Choir 4'	

COMBINATION PISTONS

THE PREFERRED REMOTE CONTROLLED CAPTURE SYSTEM ADJUSTABLE AT THE
KEYBOARD AND VISIBLY AFFECTING DRAW KNOBS

FOUR PISTONS affecting Great Organ
CANCEL
FOUR PISTONS affecting Swell Organ
CANCEL
FOUR PISTONS affecting Choir Organ
CANCEL
FOUR PISTONS affecting Positive Organ
CANCEL
FOUR PISTONS affecting Pedal Organ
CANCEL
SIX PISTONS affecting entire organ and duplicated by
Toe Stud
GENERAL CANCEL

ACCESSORIES

Balanced Swell Expression Pedal
Balanced Choir Expression Pedal
Crescendo Pedal
Crescendo Indicator
Wind Indicator
Great to Pedal Reversible Toe Stud
Tutti Pistons & Toe Stud
Tutti Indicator
Remote Control Button in Console
Music Rack Light
Pedal Board Light
Roll Top Cover for Console With Lock
Combination Lock
Motor Blower & Rectifier
Static Regulator Above Blower
Concave Pedal Clavier
Concussion Bellows for Main Wind Conductors
Separate Wind Regulators for Main Chests
Silver Contacts
Choice of Console Finish
Clock Built in Console
All Switches & Relays enclosed in Cabinets
Up to 100' ft. of organ cable, extra cable will be
furnished at \$4.00 per ft. if needed